



	Mini - FOG	Handy - FOG	N2 - FOG
<b>Main features</b>	Battery powered fogger	Portable fogger	Fogger for any application
<b>Scope of application</b>	Flow visualization at doors, enclosures, locks	Flow visualization with at least 0,2m/s	Flow visualization in turbulent flow and at very low flow speeds (even below 0,2 m/s)
<b>Fog visibility</b>	About 0,5 meter	About 2 - 3 meter	About 3 meter
<b>Fog guidance</b>	Stainless steel tubes (100 und 200mm)	With hose up to max. 3m	With hose more than 5 m
<b>Operating medium</b>	min. DI-Water	min. DI-Water	min. DI-Water and liquid nitrogen
<b>Operating time</b>	ca. 10 minutes	ca. 15 minutes at full power	About 25 minutes at full power
<b>Power supply and input</b>	Battery Operation 1 h Charging time max. 3h	230 V with external power supply 0,25 KW	230 V / 1 KW
<b>Dimensions: H x W x D</b>	200 mm x Ø 55 mm	175 x 150 x 175 mm	420 x 440 x 200 mm
<b>Weight: Empty/ Ready for use</b>	0,7 Kg / 0,75 Kg	4,5 Kg / 5 Kg	18 Kg / 19 Kg